

# R910S



Energy  
Management

## Ball valve for water for heating systems, full port

Datasheet  
0620EN 11/2022



DADO ball valve, female-female threaded connections, with drain cock with hose connection Ø 9 mm. Full port.



### ➤ Versions and product codes

| PRODUCT CODE | CONNECTIONS           | DRAIN COCK SIZE | FINISHING           | HANDLE TYPE | HANDLE COLOR | NOTES                      |
|--------------|-----------------------|-----------------|---------------------|-------------|--------------|----------------------------|
| R910SX003    | G 1/2"F x G 1/2"F     | 1/4"            | Nickel plated brass | Large lever | Red          | DADO ball, with drain cock |
| R910SX004    | G 3/4"F x G 3/4"F     | 1/4"            | Nickel plated brass | Large lever | Red          | DADO ball, with drain cock |
| R910SX005    | G 1"F x G 1"F         | 1/4"            | Nickel plated brass | Large lever | Red          | DADO ball, with drain cock |
| R910SX006    | G 1-1/4"F x G 1-1/4"F | 3/8"            | Nickel plated brass | Large lever | Red          | DADO ball, with drain cock |
| R910SX007    | G 1-1/2"F x G 1-1/2"F | 3/8"            | Nickel plated brass | Large lever | Red          | DADO ball, with drain cock |
| R910SX008    | G 2"F x G 2"F         | 3/8"            | Nickel plated brass | Large lever | Red          | DADO ball, with drain cock |

## Technical data

### Main features and materials


- Suitable for water for heating/cooling systems
- Full port
- Valve made of UNI EN 12165 CW617N nickel plated brass
- Stem with double O-Ring
- Nut with anti-corrosion coating, with guarantee seal and hologram
- Steel lever handle with anti-corrosion treatment and red PVC coating
- DADO ball
- Drain cock with hose connection Ø 9 mm

### Field of applications

- Temperature range: -20÷120 °C (-20 °C with 50 % glycol solutions)
- Max. working pressure at 20 °C with water:  
4.2 MPa (42 bar) for 1/2", 3/4"  
3.5 MPa (35 bar) for 1", 1-1/4", 1-1/2", 2"

## Dimensions and Kv

| PRODUCT CODE | DN | A [mm] | I [mm] | B [mm] | J [mm] | C [mm] | H [mm] | Kv   |
|--------------|----|--------|--------|--------|--------|--------|--------|------|
| R910SX003    | 15 | 62     | 34     | 52     | 16     | 77     | wr.25  | 13,3 |
| R910SX004    | 20 | 68     | 37     | 69     | 21     | 95     | wr.32  | 25,8 |
| R910SX005    | 25 | 82     | 44     | 77     | 25     | 95     | wr.39  | 50,9 |
| R910SX006    | 32 | 100    | 57     | 87     | 30     | 95     | wr.47  | 103  |
| R910SX007    | 40 | 110    | 62     | 108    | 37     | 137    | wr.54  | 147  |
| R910SX008    | 50 | 125    | 69     | 124    | 46     | 137    | wr.67  | 222  |



## Product specifications

### R910S

DADO ball valve, with female-female threaded connections, with drain cock with hose connection Ø 9 mm. Suitable for water for heating/cooling systems. Valve made of UNI EN 12165 CW617N nickel plated brass. Full port. Steel lever handle with anti-corrosion treatment and red PVC coating. Stem with double O-Ring. Nut with anti-corrosion coating, with guarantee seal and hologram. Temperature range: -20÷120 °C (-20 °C with 50 % glycol solutions). Max. working pressure at 20 °C with water: 4.2 MPa (42 bar) for 1/2", 3/4"; 3.5 MPa (35 bar) for 1", 1-1/4", 1-1/2", 2".

**⚠ Safety Warning.** Installation, commissioning and periodical maintenance of the product must be carried out by qualified operators in compliance with national regulations and/or local standards. A qualified installer must take all required measures, including use of Individual Protection Devices, for his and others' safety. An improper installation may damage people, animals or objects towards which Giacomini S.p.A. may not be held liable.

**♻ Package Disposal.** Carton boxes: paper recycling. Plastic bags and bubble wrap: plastic recycling.

**ℹ Additional information.** For more information, go to [giacomini.com](http://giacomini.com) or contact our technical assistance service. This document provides only general indications. Giacomini S.p.A. may change at any time, without notice and for technical or commercial reasons, the items included herewith. The information included in this technical sheet do not exempt the user from strictly complying with the rules and good practice standards in force.

**♻ Product Disposal.** Do not dispose of product as municipal waste at the end of its life cycle. Dispose of product at a special recycling platform managed by local authorities or at retailers providing this type of service.